

# **CINGO M500**



## PERFORMANCE AND FEATURES

## CINGO M500 Tracked Carrier

Hydraulic with gear pumps and orbital motors on each track and overcenter valve

#### **PERFORMANCE**

500 kg Capacity:

Honda Petrol GX200 - 4.1 kW / 5.5 HP Engine:

Starting: Manual

Engine cooling: Air

Maximum speed: 3.5 km/h

Fixed Track:

35% Maximum longitudinal gradient: 20% Maximum cross slope:

## TRANSMISSION AND

**HYDRAULIC SYSTEM** Transmission:

Transmission pumps: 2 x 11.5 litre/min - Maximum operating pressure 150 bar

Drive levers: Hydraulic systems

Parking brake: Manual

Service pump:

Auxiliary circuit oil flow rate: 1 auxiliary service line (in and out)

Auxiliary service lines: Auxiliary circuit max. pressure:

Multifunction (Merlo patent): No

Multifunction tracked carrier No

#### **WEIGHT AND DIMENSIONS**

M500D (with dumper body): 191 kg M500DP (with dumper body and self-loading bucket): 227 kg Machine weight: M500C (with farm dumper body): 210 kg


Width: 690 mm

Length: M500D/DP: 1416 mm - M500C: 1,471 mm


Maximum height: 1,126 mm

Dumper body capacity when full M500D/DP: 160 litres - M500C: 124 litres


#### Main dimensions of the various submodels:




M500DP





M500D



M500C
















Hour counter (option on request)





Data, characteristics and illustrations contained in this document are indicative and not binding. Merlo Spa pursues a policy of continuous research and development, therefore, our products may have different characteristics from those described or may undergo changes without any prior notice. The products shown may include optional equipment

## MERLO S.P.A.

Via Nazionale, 9 12010 S. Defendente di Cervasca (Cuneo) Italy Tel. +39 0171614111 Fax +39 0171684101

info@merlo.com www.merlo.com

